



PARAFUSO ALLEN - DIN 912

Diâmetro Nominal		M 1.6	M 2	M 2.5	M 3	M 4	M 5	M 6	M 8	M 10	M 12	M 14	M 16
Passo		0,35	0,40	0,45	0,50	0,70	0,80	1,00	1,25	1,50	1,75	2,00	2,00
Diâmetro da Cabeça (d)	máx.	3,0	3,8	4,5	5,5	7,0	8,5	10,0	13,0	16,0	18,0	21,0	24,0
	min.	2,86	3,62	4,32	5,32	6,78	8,28	9,78	12,73	15,73	17,73	20,67	23,67
Altura da Cabeça (k)	máx.	1,7	2,0	2,5	3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0	16,0
	min.	1,46	1,86	2,36	2,86	3,82	4,82	5,70	7,64	9,64	11,57	13,57	15,57
Tam. Nominal da Chave		1,5	1,5	2,0	2,5	3,0	4,0	5,0	6,0	8,0	10,0	12,0	14,0
(s)	máx.	1,560	1,560	2,060	2,580	3,071	4,084	5,084	6,140	8,175	10,127	12,146	14,159
	min.	1,520	1,520	2,020	2,520	3,020	4,020	5,020	6,020	8,025	10,025	12,032	14,032
Diâmetro Nominal		M 18	M 20	M 22	M 24	M 27	M 30	M 33	M 36	M 39	M 42	M 45	M 48
Passo		2,50	2,50	2,50	3,00	3,00	3,50	3,50	4,00	4,00	4,50	4,50	5,00
Diâmetro da Cabeça (d)	máx.	27,0	30,0	33,0	36,0	40,0	45,0	50,0	54,0	-	63,0	-	72,0
	min.	26,67	29,67	32,61	35,61	39,61	44,61	49,61	53,54	-	62,54	-	71,54
Altura da Cabeça (k)	máx.	18,0	20,0	22,0	24,0	27,0	30,0	33,0	36,0	-	42,0	-	48,0
	min.	17,57	19,48	21,48	23,48	26,48	29,48	32,38	35,38	-	41,38	-	47,38
Tam. Nominal da Chave		14,0	17,0	17,0	19,0	19,0	22,0	24,0	27,0	-	32,0	-	36,0
(s)	máx.	14,212	17,230	17,230	19,275	19,275	22,275	24,275	27,275	-	32,330	-	36,330
	min.	14,032	17,050	17,050	19,065	19,065	22,065	24,065	27,065	-	32,080	-	36,080

Dimensões em milímetros. Fonte: DIN 912